



In order that the present invention be more readily understood, an embodiment thereof will now be described with reference to the accompanying drawings, in which:-

Figure 1 shows a diagrammatic representation of an installation according to the present invention;

Figure 2 shows a diagrammatic side view of a portion of the installation shown in Figure 1;

Figure 3 shows a diagrammatic representation of a control box used in the installation shown in Figure 1.

Referring now to Figure 1, this shows diagrammatically a recirculating air system for purifying air in an aircraft. This is but one application of the present invention and it is suitable for use in any situation where recirculated air is being utilised eg in a ship, motor vehicle, clean room or in offices and hospitals. The enclosed space 1 is provided with an air extraction vent 2 which permits air to be withdrawn from the enclosed space 1 under action of a fan system 3 via ducting 4. Located at a suitable position along the length of the ducting 4 is an ultraviolet illumination section 5 which will be described in detail below. Additionally, if required, an air flow conditioning section 6 is also provided in the ducting 4 which is arranged to provide conventional mechanical filtering of the air flowing through the ducting 4. The thus cleaned air is returned to the enclosed space via an air inlet 8 and the operation of the fan system 3 and the ultraviolet illumination section 5 is monitored and/or controlled by a control unit 7.

As mentioned above, air extracted from the enclosed space is drawn through the air flow conditioning section 6 which is shown in more detail in Figure 2 in combination with the ultraviolet illumination section 5. The section 6 can include one or more filter sections 6a and a pre-sterilisation section 6b. The filters used can be one or more of the conventional mechanical filters such as an activated charcoal filter as well as an electrostatic filter. It is important that the

filters do not create a back pressure of any significance in the system and we have found a filter of 5 microns (G4/EU4 rating) to be sufficient. The pre-sterilisation section 6b includes an arrangement for creating slightly turbulent air flow through the ultraviolet illumination section 5. This can be achieved in a number of ways but we prefer to utilise a fixed multi bladed directional fan 9. Alternatively, the fan may be replaced by fixed shaped or planar members may be provided at an angle to the air flow in order to provide a sinuous air flow path through the section 5. The fixed shaped or planar members may be perforated or made of a porous material.

The ultraviolet illumination section 5 will now be described and is shown as being of circular cross section but it will be appreciated that any convenient cross section may be utilised which may or may not be the same cross section as used for the ducting 4. The section 5 has a cylindrical side wall 11 which encloses a central core 15 around which are mounted the individual light sources 10. The number and length of the sources 10 will depend on the air flow conditions but in the present embodiment we prefer to have eight light sources 10 uniformly disposed around the core 15 and the effect of this is to cause slightly turbulent air flow in the annular space between the core 15 and the cylindrical side wall 11. The light sources 10 are held in position such that they are spaced from the core 15 which maximises the effect of the ultraviolet light on the bacteria in the air as the air flow passes over substantially all the surface of the sources 10.

The surfaces of the wall 11 and the central core 15 are either made of or coated with material with a high reflectance to UV light. We prefer to use polished aluminium sheet which has been found to be better than polished stainless steel. The side walls 11, can be provided with an operable panel to permit maintenance of the light sources 10 and permit other access to the illumination section 5. The individual light sources 10 are attached to the core 15 in any convenient manner and are most conveniently attached by means of simple clips. Additionally, the panel in the side wall 11 may be provided with detectors (not

shown) which will detect the opening or potential opening of a panel and thus signal to the control unit 7 that the light sources 10 should be switched off. This avoids possible eye damage to maintenance personnel. The exact way in which the potential opening of the panels is signalled to the control unit is a matter of design choice and could be a micro switch or other suitable sensor which could be activated by the operation of a latch or the like on the side wall which is required to be unlatched prior to the movement of the panel itself.

Figure 3 shows a typical front panel 19 for the control unit 7 where an isolator switch 20 is shown. The control unit can be located at any convenient position but will usually be remote from the fan system 3 and illumination section 5. A key pad 21 can provide control of the illumination section 5 and also of fan speed to cater for different conditions and an LFI and hours run meter 22 is also provided which can be checked by maintenance personnel.

The proposed method is to use the ultraviolet light within the illumination section 5 in such a manner as to provide an excess of a 99% sanitation rate overall. It is also proposed to recirculate the air at regular intervals in order to improve the sanitation rate.

We have also found it to be advantageous to coat the internal surfaces of the pre-sterilisation section 6b and/or the filter section 6a with an antimicrobial agent. Preferably the agent is one which is non-leaching and non-volatile and is not consumed by microorganisms. One suitable agent is a standard antimicrobial substance (a quaternary amine) in a silane which when coated on a surface bonds to the surface to render it antimicrobially active. In particular, an agent incorporating 3-(trimethoxysilyl)-propyldimethyloctadecyl ammonium chloride as active ingredient as sold by Aegis Environments of Midland, Michigan, USA under the trade mark Aegis Microbe Shield is particularly useful.

When using an antimicrobial agent, it is preferred to use a metal "wool" as the filter in the filter section 6a and this is usually of stainless steel or other non-corroding metal. However, other filter materials such as natural or

synthetic fibres or mixtures thereof could be used.

Alternatively, or in addition, we have found it advantageous to coat the internal surfaces of the ultra-violet illumination section with the microbial agent.

Although the apparatus described above can be assembled from discrete parts or modules, it is preferred to construct the conditioning section 6 and the UV treatment section 5 as a unit so that the unit can be readily fitted into existing ducting.

By using a three stage purification process, filtration, antimicrobial treatment and UV treatment it is possible to readily achieve a sanitation rate of in excess of 99% when recirculating the air.